

Model 360

- ▶ Front loader with closed washing chamber and separate, integrated washing solvent reservoir
- ▶ Pneumatic drawer; the machine door is also the machine front; operation is only possible when the door is closed
- ▶ Drawer with powered support rollers for the impression cylinders; the support rollers are driven by an external explosion-proof gear motor
- ▶ A stainless steel drip pan underneath the drawer moves together with the drawer to keep the floor clean
- ▶ Individually configured washing and spray rinsing system
- ▶ Powerful unit of washing pump and explosion-proof motor
- ▶ Removable filter elements protect the spraying system, pumps and pipes from foreign matter
- ▶ Filling level control for the integrated solvent reservoir (operating level, max. level)
- ▶ Internal air extraction system with a powerful fan and pneumatic air inlet and air admixture valves
- ▶ Automatic washing program (PLC): washing – draining – rinsing – draining – internal air extraction; the program steps can be selected individually

Accessories

- ▶ Self-cleaning device
- ▶ Solvent cooler; alternatively: with thermostatic valve, water cooler or re-cooler
- ▶ Ambient air extraction system for the operator's workstation
- ▶ Solvent concentration measuring and regulating system for connection to an exhaust air cleaning system

Optional machine configurations

- ▶ Integration into existing rooms and cylinder logistics systems
- ▶ Continuous washing machine with 2 doors
- ▶ Model 360-W for water-based/alkaline cleaning systems

Washing machine model 360	Size 03	Size 04	Size 05
Number of impression cylinders	3	4	5
Impression cylinder diameter max. mm	300	250	300
Impression cylinder length max. mm	2000	2500	2500
Washing pump capacity m ³ /h / kW	80 / 20	105 / 28	160 / 47
Internal air extraction system m ³ /h / kW	4000 / 2.5	4000 / 2.5	4000 / 2.5
Dimensions mm	5040 x 3500 x 3100	5920 x 3500 x 3100	6800 x 4200 x 3100
Required space mm	6660 x 5500 x 3700	7980 x 5500 x 3700	9300 x 6200 x 3700
Transport clearance mm	3120 x 3400 x 2000	3560 x 3400 x 2000	4000 x 3900 x 2000

* Subject to technical changes

360

